

DP1000 Series Disposable Uncorded Earplugs

Reusable corded earplugs are embedded with an iron ball in the plug
Metal detectable used for food manufacturing

PART NO.

DP1000
PYDP1000*
PYDP100BN*
PYDP100PC*

*Pyramex retail packaged product



DP1000



PYDP1000PC

STANDARDS

ANSI/ASA S3.19-1974 | CE/UKCA EN 352:2020
NRR 32dB | SNR 38dB

GENERAL SPECIFICATIONS

Reusable: No
Metal Detectable: No
Plug Material: Foam
Plug Color: Hi-vis orange
Plug Dimension: 2.6 x 1.2 cm
Plug shape: Tapered

SIZE

One size fits most

PYDP1000



PYDP1000BN

PACKAGING

DP1000 - Sold Individually | 200 per box | 10 boxes per case
PYDP1000 - Sold in pack of 5 | 50 per box | 200 boxes per case
PYDP1000BN - 100 per bin | 3 bins per box | 6 boxes per case
PYDP1000PC - Sold by dozen | 1 per box | 18 boxes per case



PD500

i PD500 dispenser also available. Holds 500 DP1000 earplugs and can be refilled with PD500R.

PRODUCT GUIDELINES

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

- Example:
1. The environmental noise level at the ear is 92 dB(A).
 2. The NRR is 26 decibels (dB).
 3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.