

ANSI/ISEA 105

GL603C5

HPPE | Nitrile | Micro-Foam

EN388

4X43D

NITRILE DIPPED







TEAR



Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by

ANSI/ISEA 105-2015 - CUT A4 | ABRASION 4 | PUNCTURE 4 EN388 - ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 D

CE K

channeling liquids away // 13 gauge **PMXTECK** HPPE cut-resistant liner delivers cool comfort for all-day wear // Knit cuff creates a snug fit to keep out debris // Dark liner and coating hide stains // Hangtag option for retail display

Suggested Applications

Aerospace // Assembly // Construction // Furniture Manufacturing // Handling Oily Parts // HVAC

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 13 Gauge PMXTECK HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

		Inner Polybag	Outer Polybag	Case	
	GL603C5	1 Pair	12 Pair	120 Pair	
	GL603C5HT	1 Pair on Hangtag	12 Pair on Hangtags	120 Pair	
	Made in China				

Product markings may vary // Updated as of 02.24



EXPERIENCE A NEW LEVEL OF PROTECTION AND COMFORT WITH PMXTECK.

Our unique plated knit technology for gloves creates an exterior built for durability and an interior so soft and smooth you'll forget you're wearing them. With PMXTECK, comfort and safety go hand in hand.

Glove Sizing

1							
	X-Small 6	Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11	3X-Large 12
l	-		_	-			

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.



P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM