



NITRILE DIPPED



GL609C

HPPE | Nitrile | Sandy | TPR



ANSI/ISEA 105-2016 – CUT A6 | ABRASION 6 | PUNCTURE 4
 ANSI/ISEA 138-2019 – IMPACT 2
 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 |
 CUT TDM-100 E | IMPACT P

Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge **PMXTECK** HPPE cut-resistant liner delivers cool comfort for all-day wear // Custom-designed high-visibility impact protection shields the back of the hand and allows for maximum visibility // Reinforced thumb reduces stress in high-wear area // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Glass Handling // HVAC // Mining // Oil & Gas // Steel Handling // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Sandy Nitrile
Outer Liner: 13 Gauge PMXTECK HPPE
Cuff: HPPE + Latex Elastic
TPR: Thermoplastic Rubber

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



REDEFINING COMFORT IN HAND PROTECTION
PMXTECK™

EXPERIENCE A NEW LEVEL OF PROTECTION AND COMFORT WITH PMXTECK.

Our unique plated knit technology for gloves creates an exterior built for durability and an interior so soft and smooth you'll forget you're wearing them. With PMXTECK, comfort and safety go hand in hand.

Packaging

	Inner Polybag	Outer Polybag	Case	Made in China
GL609C	1 Pair	6 Pair	60 Pair	

Product markings may vary // Updated as of 02.24

Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11	3X-Large 12
------------	-------------	------------	---------------	----------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.