



Ridgeline[®] Cap Style ANSI • CSA •

ABS material – strong, yet ultra-light for seemingly weightless protection

Side clips to meet CSA standards

Low profile design – offers a low center of gravity for better balance

Available with 4- ratchet suspensions

Swinging hinge points allow you to find the most comfortable position on the back of your head

4-position harness points allows you to move the harness forward, backward, up or down – allowing for the most optimal position for ultimate comfort

Easy to grasp knob adjusts the suspension from 6½ to 8 head size

Rear padded suspension – provides additional level of comfort on the wearers' neck

Replaceable ratchet suspensions available

Replaceable sweat band - padded fabric and polyurethane foam

Vented pressure pad keeps the straps in place providing an additional level of comfort





Universal accessory slots fit cap mounted earmuffs and accessories

Ridgeline cap style hard hats pass reverse orientation, high temperature (HT) and low temperature (LT)


Non-vented hats meet Class E, G, and C safety standards for industrial head protection

Custom imprinting available

4-Point Ratchet | 4 Variations

-  HP44110C ●● White
-  HP44130C ●● Yellow
-  HP44131C ●● Hi-Vis Lime
-  HP44165C ●● Dark Blue

Cap Style 4-Point Ratchet | 1 Variation

-  HP44117C ●● Matte Black Graphite Pattern



Non-vented head protection meets ANSI Z89.1 (●), Type 1, Class E, G and C. Vented head protection meets ANSI Z89.1 (●), Type 1, and Class C. Hi-vis colors have been tested for the "HV" mark. Some options meet Canadian CSA Z94.1 - 2015 (●), Type 1, Class E, G and C standards – SEI third-party certification. For specific options visit our website or contact your sales representative.



HPR441 – 4-point Ratchet Replacement Suspension



HPRBANDR – Ridgeline Cap Style and Full Brim Hard Hat Sweat Band




Materials

- Shell: high impact acrylonitrile-butadiene-styrene (ABS)
- Suspension: high density polyethylene (HDPE) & high impact nylon
- Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

- Weight: 358 gm
- Shell thickness: 2 - 4 mm
- Dimensions: 28 cm x 22 cm x 15.2 cm
- Suspension adjust sizing: 6.5 - 8
- Suspensions: 4-point ratchet
- Styles: vented & non-vented
- Standards: ANSI/ISEA Z89.1-2014
- Types: Type 1
- Classes: non-vented Class E, G, and C | vented Class C
- Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

- Types: Type 1 offers protection to the top of the head
- Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection
- Tested and marked for reverse orientation 
- HV: meets all requirements for high visibility
- LT: provides protection at low temperatures -22°F
- HT: provides protection at high temperatures 140°F
- Date code: indicated month and year when the shell was molded – does not indicate service life  

Product Guidelines

- Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use
- Never alter or modify the shell or suspension system
- Inspect the hard hat each time before use and replace if there is ANY sign of damage
- Replace hard hat after it receives a considerable impact
- Accessories such as liners have not been tested to the requirement of this standard
- Clean only with mild soap and lukewarm water
- Store hard hat in a clean, dry place that is out of direct sunlight
- Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat
- Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage

Non-vented head protection meets ANSI Z89.1 (•), Type 1, Class E, G and C. Vented head protection meets ANSI Z89.1 (•), Type 1, and Class C. Hi-vis colors have been tested for the "HV" mark. Some options meet Canadian CSA Z94.1 - 2015 (•), Type 1, Class E, G and C standards – SEI third-party certification. For specific options visit our website or contact your sales representative.

P 800.736.8673 // F 901.861.4967 // W PYRAMEXSAFETY.COM