

# SL T2™ FACE SHIELD



## ENGINEERED PROTECTION THAT SURROUNDS

Elevate safety with the SL T2 Face Shield. Designed specifically for the SL T2 Safety Helmet, this clear face shield offers a wide field of view, providing clarity and precision in work environments. Effortlessly attaches to the SL T2 Safety Helmet for added convenience and protection.



## FEATURES

**WIDE FIELD OF VIEW:** Offers protection from potential hazards without compromising field of view, enhancing safety and productivity.

**ENHANCED SAFETY:** Constructed from robust materials, the shield frame and adapter protect and support face shield.

**USER-FRIENDLY DESIGN:** Ratchet clips make visor adjustments intuitive and efficient.

**EFFORTLESS ATTACHMENT:** Attach and detach the face shield with ease, thanks to its quick-release/connect clip design that ensures a snug and secure fit every time.

**MAXIMUM ANTI-FOG CLARITY:** Treated with H2MAX to provide maximum clarity in extreme conditions while adding abrasion and chemical resistance, ensuring durable, waterproof vision even after repeated cleaning.

**SPLASH SAFE:** Passes D3: Droplet and Splash test.

**ENGINEERED TOUGHNESS:** Meets ANSI/ISEA Z87.1-2020 + high impact standard.

 HPT2FV10 sold separately from the SL T2 Safety Helmet.



## TOOLS AT YOUR FINGERTIPS

Learn more about the SL T2 Helmet and Accessories

# SL T2™ FACE SHIELD



H2MAX



PASSES  
D3  
DROPLET AND  
SPLASH TEST

## ENGINEERED PROTECTION THAT SURROUNDS

Elevate safety with the SL T2 Face Shield. Designed specifically for the SL T2 Safety Helmet, this clear face shield offers a wide field of view, providing clarity and precision in work environments. Effortlessly attaches to the SL T2 Safety Helmet for added convenience and protection.

## FACE SHIELD

● HPT2FV10

Clear AF



## MATERIALS

Lens: PC [Polycarbonate]

Frame: ABS [Acrylonitrile Butadiene Styrene] Plastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

## GENERAL SPECIFICATIONS

Weight: 145.5g

Overall Length: 227mm

Overall Width: 133mm

Lens Thickness: 1mm

Lens Base: 8.48mm

Vertical Lens Measurement: 177.5mm

## MARKINGS

Standard: ANSI/ISEA Z87.1-2020 +

Part No.	Lens Marking	Lens Marking Symbols
HPT2FV10	KJ Z87+ U4 X D3	KJ: Manufacturer's mark Z87: ANSI/ISEA standard for eye and face protection devices +: High impact U4: .04% max effective far UV • .5% max near UV D3: Tested droplet and splash test X: Tested anti-fog

Product markings may vary // Updated as of 05.24

## INSTRUCTIONS

### TO ATTACH FACE SHIELD TO HELMET

1. Push the clips into the front side accessory slots until you hear a click indicating it's secure.

### TO REMOVE FACE SHIELD FROM CLIPS

1. Press the button labeled "PUSH" at the top of the clip.
2. Pull the shield out of the clip.

### TO REMOVE CLIPS FROM HELMET

1. Simply pull up on the clips to detach them from accessory slots.

### TO REMOVE FACE SHIELD FROM ADAPTER

1. Press the button labeled "PUSH" at the top of the clip.
2. Pull the shield out of the clip.