SL T2[™] SAFETY HELMET

ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SL T2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SL T2 accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.



ABS SHELL

SSORY VENTED

ACCESSORY COMPATIBLE



COMFORTABLE PADDING RATCHET SUSPENSION



PYRAMEX[®] ♥ ₩ ↔ ∧ 0 ↔ ☆ △ P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

FEATURES

ADVANCED IMPACT ABSORPTION: EPS foam liner absorbs forces from all angles for unparalleled protection.
ROBUST, LIGHTWEIGHT SHELL: ABS shell ensures durable, lightweight protection.
ACCESSORY COMPATIBILITY: Pair with SL T2 accessories for tailored safety solutions.
COMFORTABLE PADDING: Designed with strategically placed soft padding to ensure all-day comfort.
EFFORTLESS ADJUSTMENT: Ratchet suspension easily adjusts to provide a perfect fit across all head sizes.
SECURE-FIT DESIGN: 4-point cross-over chin strap with quick-release buckle for a secure, comfortable fit.
ENGINEERED TOUGHNESS: Meets ANSI/ISEA Z89.1-2014 (R2019) Type II standard to ensure durability and confidence in performance.



SCAN HERE TO EXPLORE THE SL T2 HELMET AND ACCESSORIES

SL T2[™] SAFETY HELMET

ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SL T2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SL T2 accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.



ABS SHELL

ACCESSORY V COMPATIBLE 0





COMFORTABLE PADDING RATCHET



MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic		
Inner Lining: Dual Density EPS (Expanded Polystyrene) Foam		
Sweatband: Fleece + Foam		
Chin Strap: Nylon + Silicone + PS (Polystyrene) + PP (Polypropylene)		
Buckle: POM (Polyoxymethylene)		
Suspension: PP (Polypropylene)		

 \triangle WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

GENERAL SPECIFICATIONS

Weight: 510g	
Shell Thickness: 2.5mm	
Dimensions: 10.25" x 8.5" x 7"	
Suspension Adjust Sizing: 6 ⁵ /8 to 7 ⁷ /8	
Suspension: Adjustable with Ratcheting Wheel	
Chin Strap: 4-Point Cross-Over Adjustable	

NON-VENTED

Ratchet Suspension | 5 Variations

HPT261110	White
HPT261111	Black
HPT261162	Light B
HPT261130	Yellow
HPT261140	Orange



MARKINGS

Standard: ANSI/ISEA Z89.1-2014 (R2019)		
Type: Type II Safety Helmet		
Class: Non-Vented – Class E (Electrical) Rated for 20,000 Volts, Vented – Class C (Conductive) Does Not Offer Electrical Protection		
LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F		
Date Code: Indicates month and year shell was molded - does not indicate service life.		

Blue

Product markings may vary // Updated as of 05.24

PRODUCT GUIDELINES

Maximum shelf life of 5 years (shell) from the time of first use - whichever occurs first.

Never alter or modify the shell, suspension, or chin strap.

Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

Replace the helmet after it receives a considerable impact.

Only use genuine $\ensuremath{\mathsf{Pyramex}}$ accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water.

Store helmet in a clean, dry place that is out of direct sunlight.

Do not use paints, chemicals, adhesives, gasoline, or similar substances on the helmet.

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.

PYRAMEX° 💐 🖬 🕶 🗢 🛛 🖓 🌤 🖄

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM