


TRUFLEX™

TAILORED FIT FOR EVERY FACE: GLASSES DESIGNED FOR DIVERSITY

Experience personalized comfort with TruFlex™ safety glasses. Designed with a vented frame, they offer enhanced airflow, preventing fogging and ensuring clear vision in any environment. Featuring a customizable nose piece and temples, they ensure a tailored fit for every face, providing unmatched comfort and protection.



FEATURES

All-Day Comfort: Designed with lightweight, half frames to provide a comfortable fit and clear vision, striking the ideal balance between protection and aesthetics

Expanded Field of Vision: Wraparound polycarbonate lens is scratch-resistant, providing clear vision and UV protection against harmful rays

Tailored Fit: Articulating, adjustable nose piece accommodates various nasal bridge sizes, ensuring optimal fit and comfort, while vented, adjustable temples allow for the perfect fit for side eye coverage and protection

Air Flow Advantage: Vented frames ensure a crystal-clear view by promoting air circulation to prevent lens fogging, even in the most demanding environments

Supreme Anti-Fog Clarity: (Select styles) The lens, treated with H2X, offers comprehensive protection with anti-fog, anti-scratch, and anti-static properties, while its durable, waterproof formula guarantees clear vision even after repeated cleaning

Built Tough: Meets ANSI/ISEA Z87.1-2020 +,  certified to CAN/CSA Z94.3-20 for eye and face protection devices



SGL113

TRUFLEX™

TAILORED FIT FOR EVERY FACE: GLASSES DESIGNED FOR DIVERSITY

Experience personalized comfort with TruFlex™ safety glasses. Designed with a vented frame, they offer enhanced airflow, preventing fogging and ensuring clear vision in any environment. Featuring a customizable nose piece and temples, they ensure a tailored fit for every face, providing unmatched comfort and protection.



H2X
OPTIONS



AF
ANTI-FOG
OPTIONS



ADJUSTABLE
NOSE PIECE



VENTED
FRAME



ADJUSTABLE
TEMPLES

VARIATIONS



Black and Gray Frame

- SBG11310DT Clear H2X AF
- SBG11320DT Gray H2X AF
- SBG11380DT I/O Mirror AF



Gray and Lime Frame

- SGL11310DT Clear H2X AF
- SGL11320DT Gray H2X AF
- SGL11380DT I/O Mirror AF

MATERIALS

Lens	Frame	Nose Piece	Hinge	Temples	Screw
Polycarbonate	Polycarbonate	Polycarbonate + Thermoplastic Rubber (TPR)	Nylon	Polycarbonate + Thermoplastic Elastomer (TPE)	Stainless Steel

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SBG11310DT	P Z87 + U6	P Z87 + / P c SEI Z94.3	P: Manufacturer's Mark	P: Manufacturer's Mark	Weight: 23.8 gm
SBG11320DT	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	+: High Impact	Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices	PD: 64 mm
SBG11380DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	U6: .01% Max Effective Far UV .1% Max Near UV	+: High Impact	Lens Base: 8 Curve
SGL11310DT	P Z87 + U6	P Z87 + / P c SEI Z94.3	L1.7: 55% Max Visible Light	Z94.3: Certified for CAN/CSA Z94.3-20 Standard for Eye and Face Protection Devices	Lens Size Diagonal: 75.9 mm
SGL11320DT	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	L2.5: 29% Max Visible Light		Lens Size Vertical: 43.8 mm
SGL11380DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3			Lens Thickness: 1.8 mm

Product markings may vary // Updated as of 09.24

Overall Length (Lens - Tip): 164 mm
Overall Width (Hinge - Hinge): 134.7 mm
Closest point between temples: 84.4 mm
Closest point between lens: 12 mm