

# Venture II® Readers

ANSI/ISEA • CE/UKCA • CAN/CSA •



Temples adjust to four different lengths // Rubber nosepiece secures the glass and prevents slipping

## Black Frame | 8 Variations

●	ESB1810R10	●●●	Clear	+1.0 Mag
●	ESB1810R15	●●●	Clear	+1.5 Mag
●	ESB1810R15T	●●●	Clear H2X AF	+1.5 Mag
●	ESB1810R20	●●●	Clear	+2.0 Mag
●	ESB1810R20T	●●●	Clear H2X AF	+2.0 Mag
●	ESB1810R25	●●●	Clear	+2.5 Mag
●	ESB1810R25T	●●●	Clear H2X AF	+2.5 Mag
●	ESB1810R30	●●●	Clear	+3.0 Mag



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
ESB1810R10	2 C - 1.2 P 1 FT CE	+1.00 CE P EN166 FT UKCA	Weight: 27 gm	Lens: polycarbonate
ESB1810R15	2 C - 1.2 P 1 FT CE	+1.50 CE P EN166 FT UKCA	PD: 68 mm	Frame: nylon 6-6 - poly(hexamethylene adipamide)
ESB1810R15T	2 C - 1.2 P 1 FTN CE	+1.50 CE P EN166 FT UKCA	Bridge: 10.5 mm	Temples: polycarbonate & thermoplastic elastomers (TPE)
ESB1810R20	2 C - 1.2 P 1 FT CE	+2.00 CE P EN166 FT UKCA	Lens base: 9.75 curve	Hinge: polycarbonate + nylon
ESB1810R20T	2 C - 1.2 P 1 FTN CE	+2.00 CE P EN166 FT UKCA	Lens size diagonal: 56 mm	Screw: stainless steel
ESB1810R25	2 C - 1.2 P 1 FT CE	+2.50 CE P EN166 FT UKCA	Lens size vertical: 45 mm	Side shields: polycarbonate
ESB1810R25T	2 C - 1.2 P 1 FTN CE	+2.50 CE P EN166 FT UKCA	Lens thickness: 2.2 mm	Nosepiece: polycarbonate + thermoplastic rubbers (TPR)
ESB1810R30	2 C - 1.2 P 1 FT CE	+3.00 CE P EN166 FT UKCA	Overall length (lens - tip): 150-163 mm	
			Overall width (hinge - hinge): 142 mm	

## Lens Marking Symbols

### Code - field of use

2 or 3: UV filter

5 or 6: Solar filter

### Colour Perception

C: Unimpaired colour perception

### Protection Class

1.2 - 6: Degree of visible light filtration

### Optical Class

1: High optical quality - no optical distortion

### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

T: Impact protection at extreme temperature conditions

### Symbols

P: Manufacturer's mark

K: Resistance to surface damage by fine particles

N: Filter with anti-fog

CE: Certification for European Union

## Temple Marking Symbols

### Symbols

+1.00: magnification of +1.0

+1.50: magnification of +1.5

+2.00: magnification of +2.0

+2.50: magnification of +2.5

+3.00: magnification of +3.0

CE: Certification for European Union

P: Manufacturer's mark

EN166: Standard for protective eyewear

UKCA: Certification for United Kingdom

### Mechanical Strength

F: Low energy impact

T: Impact protection at extreme temperature conditions